

## LASER CONSUMABLE REFERENCE SHEET LV-PLUS II 3015 45CF-R SERIES

ITEM	DESCRIPTION	PART NUMBER	
<b>PROCESSING LENS</b>	Lens 2.0" dia x. 7.5"	<b>W510</b>	
	Lens 2.0" dia x. 5.0"	<b>W505</b>	
<b>BEND MIRRORS</b>	<b>Resonator type</b>	<b>45CF-R</b>	
	<b>Name</b>	<b>Description</b>	<b>Part number</b>
	<b>RBM#1</b>	PHASE LOCK 60mm DIA. x t15	<b>W645</b>
	<b>RBM#2</b>	MIRROR LV TRZ-2 60mm DIA x15 t	<b>W644</b>
	<b>BM#1</b>	MIRROR LV TRZ-2 60mm DIA x15 t	<b>W644</b>
	<b>BM#2</b>	MIRROR LV TRZ-2 60mm DIA x15 t	<b>W644</b>
	<b>Beam Optimizer</b>	B/O FLEX MIRROR DIA.60mmxt3mm	<b>LAY2700</b>
	<b>BM#4</b>	MIRROR LV TRZ-2 60mm DIA x15 t	<b>W644</b>
	<b>BM#5</b>	MIRROR LV TRZ-2 60mm DIA x15 t	<b>W644</b>
	<b>BM#6</b>	MIRROR LV TRZ-2 60mm DIA x15 t	<b>W644</b>
	<b>BM#7</b>	MIRROR TRZ-2 76.2mm DIA. x t15	<b>W643</b>
	<b>BM#8</b>	PHASE RETARDER 76.2MM DIA xt15	<b>LC51600</b>
	<b>BM#9</b>	MIRROR TRZ-2 76.2mm DIA. x t15	<b>W643</b>
	<b>BM#10</b>	MIRROR TRZ-2 76.2mm DIA. x t15	<b>W643</b>
<b>RESONATOR OPTICS</b>	<b>PR-</b>	40 CFX PR HOLDER	<b>LC63800</b>
	<b>TR-</b>	TR 20PRZ1.5-99-0247	<b>R003</b>
	<b>STR-</b>	POLARIZATION LOCK MIRROR LZ/P	<b>LA68000</b>
	<b>ITR(S)-</b>	ITR MIRROR 28mm diameter, 6mm	<b>R106</b>
<b>NOZZLES</b>	<b>HEAD TYPE</b>	<b>PH-X</b>	<b>DOUBLE NOZZLE</b>
	<b>W1626C</b>	SINGLE PCS NOZZLE 1.0MM	<b>W390</b> DBL NOZZLE INSERT-4
	<b>W1627C</b>	SINGLE PCS NOZZLE 1.2MM	<b>W270</b> DBL NOZZLE INSERT-8
			<b>W270.2</b> Double Nozzle inert-8 2mm
	<b>W1628</b>	SINGLE PCS NOZZLE 1.5MM	<b>W387</b> DBL NOZZLE INSERT-12
	<b>W1661</b>	SINGLE PCS NOZZLE 1.7MM	<b>W388</b> DBL NOZZLE INSERT-16
	<b>W1629</b>	SINGLE PCS NOZZLE 2.0MM	<b>LU91900</b> PH-X Side Nozzle Dia 8mm
	<b>W1630</b>	SINGLE PCS NOZZLE 2.5MM	<b>W389</b> DBL NOZZLE INSERT-20
	<b>W1664</b>	SINGLE PCS NOZZLE 3.0MM	<b>W515</b> DBL NOZZLE INSERT-24
	<b>W1665</b>	SINGLE PCS NOZZLE 3.5MM	<b>W290</b> O-RING 4DP16
	<b>W1666</b>	SINGLE PCS NOZZLE 4.0MM	<b>LQ19900</b> Brilliant Cut 8 hole Au Coating
	<b>W1662</b>	SINGLE PCS NOZZLE 4.5MM	<b>LQ20000</b> Brilliant Cut 24 hole Au Coating
	<b>W1663</b>	SINGLE PCS NOZZLE 5.0MM	<b>AL479MMS</b> Brilliant Cut DIA 4.0mm outer
	<b>AL238MMS</b>	Outside double nozzle	<b>AL480MMS</b> Brilliant Cut DIA 7.0mm outer
<b>MISC</b>	<b>Part#</b>	<b>Description</b>	
	<b>A403A</b>	AMERI WATER REGN CERT. 3101C	
	<b>A407</b>	PREFILTER CARTRIDGE 8475	
	<b>A409A</b>	START UP RESIN PACKS 4101	
	<b>LC47400</b>	LOCATING PIN JPZA5-6.00 ON LV	
	<b>LD23100</b>	Steel Locating Pin	
	<b>LC50700</b>	LV BREAKAWAY PPS BOLT M6X25 TAN	
	<b>PHX-INS-A</b>	SHORT INSULATOR FOR LV (PH-X)	

Corporate Headquarters • MC Machinery Systems, Inc. • 85 Northwest Point • Elk Grove Village, IL 60191  
888/297-9895 • Fax: 630/616/2954 • email: [cpg@mcmachinery.com](mailto:cpg@mcmachinery.com)

